

1. Unique identification code of the product-type: **ONDUTEX® 300 BASE**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Geotextile (S + F)**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Onduline**  
**24, quai Galliéni**  
**F- 92 150 Suresnes – France**  
**www.onduline.com**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
- 6.a. In case of the declaration of performance concerning a construction product covered by a harmonised standard : **EN 13249:2016, EN 13250:2016, EN 13251:2016, EN 13252:2016, EN 13253:2016, EN 13254:2016, EN 13255:2016, EN 13257:2016, EN 13265:2016**
- 6.b. European Assessment document: **Not applicable**  
 European Technical Assessment: **Not applicable**  
Notified Body: **No. 0799 Kiwa GmbH TBU performed initial inspection of the manufacturing plant and of factory production control and continuous surveillance and issued certificate of conformity No. 0799-CPR-71.**
7. Declared performance

Essential characteristics	Performance	Tolerance	Appropriate technical documentation
<b>Tensile strength MD</b>	3,5 kN/m	- 1,0 kN/m	EN ISO 10319
<b>Tensile strength CMD</b>	3,5 kN/m	- 1,0 kN/m	EN ISO 10319
<b>Elongation MD</b>	65%	[-20 ; +20] %	EN ISO 10319
<b>Elongation CMD</b>	65%	[-20 ; +20] %	EN ISO 10319
<b>Dynamic perforation resistance</b>	22 mm	+ 8 mm	EN ISO 13433
<b>Resistance to static puncture</b>	700 N	- 150 N	EN ISO 12236
<b>Opening size</b>	0,085 mm	[- 0,045 ; + 0,045] mm	EN ISO 12956
<b>Water permeability / v-index</b>	0,085 m/s	- 0,045 m/s	EN ISO 11058
<b>Weather resistance and durability</b>	To be covered within 1 day after installation Durable for 5 years in natural soils with 4 <= pH <= 9 and soil temperatures <= 25°C.		Annex B EN 13249 :2016 EN 13255 :2016 EN 13257 :2016 EN 13265 :2016
<b>Mass per unit area</b>	300 g/m <sup>2</sup>	[-60 ; +60] g/m <sup>2</sup>	EN ISO 9864
<b>Thickness</b>	3,0 mm	[- 0,75 ; + 0,75] mm	EN ISO 9863-1
<b>Dangerous substances</b>	NO (*)	-	-

\* the product does not contain dangerous substances referred to Art 31 & 33 of the REACH regulations.

8. Appropriate Technical Documentation and/or Specific Technical documentation : **No**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Christophe ROHART**  
**Industrial and R&D Director**



Suresnes, 02/02/2022

rev.1