

1. Unique identification code of the product-type: **ONDUTEX®200 BASE**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Geotextile (S + F)

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Onduline
24, quai Galliéni
F- 92 150 Suresnes – France
www.onduline.com

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
- 6.a. In case of the declaration of performance concerning a construction product covered by a harmonised standard : **EN 13249:2016, EN 13250:2016, EN 13251:2016, EN 13252:2016, EN 13253:2016, EN 13254:2016, EN 13255:2016, EN 13257:2016, EN 13265:2016**

- 6.b European Assessment document: **Not applicable**
 European Technical Assessment: **Not applicable**
Notified Body: **No. 0799 Kiwa GmbH TBU performed initial inspection of the manufacturing plant and of factory production control and continuous surveillance and issued certificate of conformity No. 0799-CPR-71.**

7. Declared performance

Essential characteristics	Performance	Tolerance	Appropriate technical documentation
Tensile strength MD	2,0 kN/m	- 1,0 kN/m	EN ISO 10319
Tensile strength CMD	2,5 kN/m	- 1,0 kN/m	EN ISO 10319
Elongation MD	65%	[-20 ; +20] %	EN ISO 10319
Elongation CMD	65%	[-20 ; +20] %	EN ISO 10319
Dynamic perforation resistance	30 mm	+ 15 mm	EN ISO 13433
Resistance to static puncture	400 N	- 100 N	EN ISO 12236
Opening size	0,110 mm	[- 0,05 ; + 0,05] mm	EN ISO 12956
Water permeability / v-index	0,110 m/s	- 0,05 m/s	EN ISO 11058
Weather resistance and durability	To be covered within 1 day after installation Durable for 5 years in natural soils with 4 <= pH <= 9 and soil temperatures <= 25°C.		Annex B EN 13249 :2016 EN 13255 :2016 EN 13257 :2016 EN 13265 :2016
Mass per unit area	200 g/m ²	[-40 ; +40] g/m ²	EN ISO 9864
Thickness	2,0 mm	[- 0,5 ; + 0,5] mm	EN ISO 9863-1
Dangerous substances	NO (*)	-	-

* the product does not contain dangerous substances referred to Art 31 & 33 of the REACH regulations.

8. Appropriate Technical Documentation and/or Specific Technical documentation : **No**
 The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Christophe ROHART
 Industrial and R&D Director



Suresnes, 02/02/2022

rev.1