

Declaration of Performance

N° DoP: 2023-005 SA47



Unique identification code of the product-type:

**ONDUTISS® AIR NEO UVFR 220, ONDUTISS® AIR NEO UVFR 220 T,
ONDUTISS® AIR NEO UVFR 220 TT**

Intended use/es:

Flexible sheets for underlays for roofs - Under roof covering of discontinuous roofs of buildings

Manufacturer:

Onduline
24, quai Gallieni
92150 Suresnes - France

System/s of AVCP:

System 3

Harmonised standard :

EN 13859-1:2010

Notified body/ies:

**0761 - Materialprüfanstalt für das Bauwesen (MPA BS)
0799 - Kiwa GmbH Niederlassung TBU**

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	B s1 d0	-	-	EN 13859-1:2010
Watertightness	W1	-	-	
Water vapour resistance factor Sd (m)	0,15	-0,03	+0,03	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	370 / 370	-30	+100	
Elongation at maximum load (longitudinal/transverse direction) (%)	30 / 30	-10	+20	
Resistance to tearing (longitudinal/transverse direction)	180 / 180	-20	+40	
Flexibility at low temperature (pliability) (°C)	>-20	-	-	
Durability of resistance to water penetration	W1	-	-	
Durability of tensile strength (longitudinal/transverse direction)	370 / 370	-30	+100	
Durability of elongation (longitudinal/transverse direction)	30 / 30	-10	+20	
Dangerous substances	NPD			

NPD* : No Performance Declared

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v03

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay Tawile', is written over a horizontal line.

Nay TAWILE
Suresnes, le 04/03/2024